Signal Matrix SMU-3000

Features

- Extremely broad band
- Very high intercept points
- Good noise figure
- Compact units for rack mount
- 2 or 4 port versions
- HF/VHF and VFH/UHF version
- Extremely rugged
- Meets military quality and environmental specifications



Product description

The unit is a high performance state of the art signal selector based on advanced high-dynamic range signal routing and amplification technology. It could be used as antenna selector or selecting any kind of signals in measurement or receiving systems in its operation range with high-dynamic range and low-distortion.

This signal routing unit reflect Sagax's ability to design and produce extremely broad band systems for surveillance and multiple frequency coverage.

The information contained herein is believed to be accurate and reliable. Sagax assumes no responsibility for inaccuracies or omissions. Specifications subject to change without prior notice. All Trademarks are the property of their respective owners.



Insertion loss



Return loss at input and out port

Specification summary

Signal routing data	
Frequency range	HF/VHF: 1.5-500MHz VHF/UHF: 20-3000MHz
Number of inputs	2 (SMU-3000-2-X) 4 (SMU-3000-4-X)
Number of outputs	2 (SMU-3000-X-2) 4 (SMU-3000-X-4)
Input impedance	50 ohm
Output impedance	50 ohm
VSWR of input ports	MAX. 1:2.0
VSWR of output ports	MAX. 1:2.0
Gain	0 dB +2dB/-6dB
Input power	15 dBm max.
Noise figure	6 dB typ.
Input connectors	HF/VHF: BNC-F VHF/UHF: SMA-F
Output connectors	HF/VHF: BNC-F VHF/UHF: SMA-F
General data	
Environmental requirements	MIL STD 810D
Electromagnetic compatibility	MIL STD 461C
Power supply	12V DC operation Reverse polarity protected
Power consumption	15 W max.
Packaging	-2-2: 1U 19” (H44mm, W200mm, L260mm) -4-4: 2U 19” (H88mm, W200mm, L260mm)
Weight	2.5 kg
Operating temperature	-10°C to +50°C
Storage temperature	-30°C to +70°C
Relative humidity	95 maximum non condensing at 40°C